



**MADERA UNIFIED
SCHOOL DISTRICT**
1902 Howard Road
Madera CA 93637
(559) 675-4500
(559) 675-1186 Fax
www.madera.k12.ca.us

Board of Trustees:

President:

Al Galvez

Clerk:

Robert E. Garibay

Trustees:

Ricardo Arredondo

Brent Fernandes

Ed McIntyre

Ray G. Seibert

Maria Velarde-Garcia

SUPERINTENDENT:

Edward C. González

May 12, 2016

Addendum No. 2

Tennis Court Maintenance, Repair and Resurface at
MSHS and MHS-Bid No. 040716

NOTICE TO ALL VENDORS:

This Addendum is attached to and made a part of the above entitled specifications for Madera Unified School District for Bid No. 040716 with a due date of May ~~6-19~~, 2016@ 10:01 a.m.

All changes and/or clarifications will appear in bold type and deletions will be struck out within a sentence.

- Questions due no later than May ~~3-16~~ @ 9:00 am, 2016
- **Contractor must poses a City of Madera Business License**
- General Site Work:

Install expansion joints

Expansion Joints:

Expansion Joint Sealant-The sealant shall be a two-component, self-leveling, polyurethane elastomeric sealant, to match the tennis court surfacing colors, similar to "Sikaflex-2c, SL as manufactured by Sika Corporation or approved equal.

Backer Rod Material-The material shall be non-absorbent and specifically recommended by the sealant manufacturer

Masking Materials-The material shall be an appropriate masking tape which will effectively prevent application of sealant on surfaces that are not scheduled to receive it and removable without damage to substrate or staining.

Preparation-Trim existing expansion joint material to a depth that will provide a ¼" space from the top of the slab to the top of the backer rod to be replaced in the joint. The contractor shall remove the loose debris, trash and organic material in the expansion joints. Mask adjacent tennis court surfaces to prevent contact of the sealant with adjoining surfaces. Remove tape after placement of sealant without disturbing joint seal.

Install joint backing material in expansion joints to a depth that will provide a ¼" space from the top of the concrete slab to the top of the backer rod to be placed in the joint.

Install in accordance with the manufacturer's written instructions.

Install joint sealant into the prepared expansion joints as recommended by the manufacturers written instructions. Fill the

expansion joints until the level of the sealant matches the adjacent tennis court surface grade.

- Madera South High School-Scope of Work:

In surface preparation, (utilize ~~Armor Crack Repair System Products~~ Advantage **Crackflex or equal to product**)

Apply 2" wide white tennis court striping-in accordance with specification of the United States Tennis Association (USTA)-Must be hand painted?

Remove and replace expansion joint caulking ~~(if applicable)~~

Apply textured acrylic resurfacer ~~per manufactures instructions~~ **(1 coat)**

Apply coat of colored textured 100% acrylic latex **(2 coats)**

Apply approved top coat ~~per manufacturer instructions~~ **(1 coat)**

Colors:

Play Area-~~Purple~~ **match to existing color**

Out of Bounds-~~Green~~ **match to existing color**

- Madera High School-Scope of Work:

Remove and replace expansion joint caulking ~~(if applicable)~~

Signature: _____

Print Name: _____

Date: _____