

Big Splash! IO164

see inside for complete specifications

Construction Pattern Loop	Pile Fiber & Type Eco Solution Q [®] Nylon	Dye Method 80% Solution Dyed 20% Yarn Dyed	Gauge 1/8th	Stitches Per Inch 10:0	Tufted Pile Height 5/32" (.156")	Tufted Yarn Weight 26 oz.	Width 12'	Secondary Backing Ultraloc [®] Pattern
------------------------------	--	--	----------------	---------------------------	-------------------------------------	------------------------------	--------------	--

Big Splash! Modular IO166

see inside for complete specifications

Construction Pattern Loop	Pile Fiber & Type Eco Solution Q [®] Nylon	Dye Method 80% Solution Dyed 20% Yarn Dyed	Gauge 1/10th	Stitches Per Inch 10:0	Tufted Pile Height 5/32" (.156")	Tufted Yarn Weight 26 oz.	Tile Size 24" W X 24" L	Secondary Backing EcoWorx [®]
------------------------------	--	--	-----------------	---------------------------	-------------------------------------	------------------------------	----------------------------	---

Each carton contains 12 tiles
(5.33 square yards/48 square ft.)
Recommended installation method
monolithic



Big Splash! EPBL IO165

see inside for complete specifications

Construction Pattern Loop	Pile Fiber & Type Eco Solution Q [®] Nylon	Dye Method 80% Solution Dyed 20% Yarn Dyed	Gauge 1/8th	Stitches Per Inch 10:0	Tufted Pile Height 5/32" (.156")	Tufted Yarn Weight 26 oz.	Width 12'	Secondary Backing EcoWorx Performance Broadloom [™]
------------------------------	--	--	----------------	---------------------------	-------------------------------------	------------------------------	--------------	---

Basis for Specifications

Product specifications are based on averages resulting from normal manufacturing processes and may vary within normal industry tolerances. Product performance is not affected by such variances.

This carpet is produced solely for the use as a floor covering and is not recommended for any other use.

Colors may vary slightly from dye lot to dye lot.

As carpet is a textile material, a perfect pattern match is not guaranteed. Please refer to The New Pattern & Designweave's recommended installation guidelines and techniques for a suitable match.

The New Pattern & Designweave reserves the right to make changes in raw materials without notice where performance standards are maintained or exceeded.

Walk-off mats are recommended at building entrances.

Chair pads are recommended.

The installation process is critical for a satisfactory project. Consult The New Pattern & Designweave's installation manuals and in-series for installation assistance.

Shown with Color Choice available
in Broadloom and Modular



This sample folder is produced from recycled, recyclable or biodegradable materials. When products are discontinued, please join The New Pattern & Designweave in reducing landfill waste by removing samples and placing the empty folder into a paperboard recycling container.



Product contains a minimum of 25% recycled content and/or is 100% recyclable. The product consists of one or a combination of the following: Eco Solution Q[®], EcoWorx[®] and/or Ecoblogix[®] backing.



Tested and approved in accordance by the Carpet and Rug Institute's indoor Air Quality Testing and Labeling Program. For more information call 1-800-982-8846.


SHAW GREENEDGE INITIATIVES

004 | Eco Solution Q[®]

Paseo Modular

Product Specifications

Collection Name	Beyond The Door	
Style Number	I0316	
Product Type	Modular	
Construction	Multi-Level Pattern Loop	
Fiber Type	Eco Solution Q® Nylon	
Dye Method	100% Solution Dyed	
	English	Metric
Gauge	1/12	47.24 per 10 cm
Stitches Per Inch	11	43.31 per 10 cm
Tufted Pile Height	3/32" low - 6/32" high	2.38mm - 4.76mm
Tufted Yarn Weight	32.0	1,084.98 g/m²
Finished Pile Thickness	0.134	3.40 mm
Product Size	24" x 24"	60.96 cm x 60.96 cm
Density	8,597	16.01 kilotex
Protective Treatments	SSP® Shaw Soil Protection	
Primary Backing	Non-Woven Synthetic	
Secondary Backing	EcoWorx® Tile	
GSA Approved Product	Yes	




Performance Specifications

Traffic Class	Severe (TARR)
Antimicrobial Assessment	Passes (AATCC-174) (When installed using Shaw 1036 adhesive)
Methanamine Pill Test	Passes (DOCF-1-70)
Radiant Panel	Class I
NBS Smoke	Less than 450 (ASTM-E-662)
Electrostatic Propensity	Less than 3.5 kV (AATCC-134)
CRI Green Label Plus	Certified GLP9968
ADA Compliance	This product meets the guidelines as set forth in the Americans with Disabilities Act for minimum static coefficient of friction of 0.6 for accessible routes.

Warranty Information

Lifetime Commercial Limited

Installation Methods



because flooring matters.



Environmental Specifications

Recyclability	100% recyclable
---------------	-----------------

Materials

Ingredients

Surface Treatments	non c8 fluorocarbon chemistry
does not contain PVC, phthalates, or PBD/PBDE	

Recycled Content

Total Recycled Content (by weight)	34.7 %
Pre-Consumer	34.7 %
Post-Consumer	0.0 %
Bio-Based/Rapidly Renewable Content (By Weight)	0.0 %

Packaging	100% Recyclable
Location of manufacture	Cartersville, Ga. 30120, USA

Meets or exceeds all local and national regulations in country of manufacture.
Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.
Recycled content is calculated using system allocation, mass balance, and direct insertion.
The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

Third Party Certifications

MBDC Cradle to Cradle	Silver Certified
NSF 140	gold certified
CRI Green Label Plus	Certified GLP9968
USGBC LEED	contributes
Building Research Establishment	certified
Good Environmental Choice Australia	certified
Singapore Green Label	Certified 039-003

because flooring matters.